



PCB LAYOUT
Ref.

MATERIALS:

- HOUSING-DSM STANYL TE250F6 (NYLON-46)
HEAT DEFLECTION TEMP,290°
BLACK COLOR,UL94V-0
- CONTACTS-0.35mm THICK PHOS-BRONZE PLATED
WITH HARD GOLD AND GOLD FLASH IN
SOLDER AREA.

CAVITY CONFIRMS TO FCC RULES AND REGULATIONS
PART 68,SUBPART F.

Ordering Information

AJT18L	8	8	1	X-0	X 0
Type	Positions	Contacts	Ports	Plating 3 =30u" 4 =50u"	No Shield

	LED1	LED2		LED1	LED2
1=	Yellow	Green	5=	Green	Red
2=	Green	Green	6=	Red	Green
3=	Green	Yellow	7=	Yellow	Yellow
4=	Green	Orange	8=	Grn/Ylw	Grn/Ylw
			9=	Red/Grn	Red/Grn

Tolerance
unless otherwise specified

.0 ± .25
.00 ± .13
.000 ± .05

	P/N: AJT18L881X-0X0
	Desc.: Side entry, unshielded, LED, thru hole modular jack
Date: 7-07-09	Drawn By: Donna Mears
Dimensions in mm	Verified By: Mike Balekdjian