

Data sheet

RP03AxxHBLC Type 213

Page 1/6

P/N

312132xx

xx=number of poles


2023/06/26

Version: M

Illustrations



Dimensional drawing



See enlarged drawings at the end of document

Product specification

- screw type terminal block, pluggable
- centerline 10.16 mm, direction of connection 90°
- lift system, fittable without loss of poles
- color black



Data sheet RP03AxxHBLC Type 213

Page 2/6

P/N
312132xx

xx=number of poles

2023/06/26

Version: M

Technical Data

General Data			
Tightening torque SEV	0.5 Nm		
Tightening torque UL	4.4 lb-in		
min. number of poles	2		
max. number of poles	12		
Insulating material class	CTI 600		
clearance/creepage dist.	8.28 mm		
Protection category	IP20		
Min. insul. strip length	8 mm		
Rated current	12 A		
Overvoltage category	III	III	II
Pollution degree	3	2	2
Rated voltage	160 V	400 V	400 V
Rated test voltage	2.5 kV	2.5 kV	2.5 kV
Terminal data			
rat.wiring solid AWGmax	0.08 mm² - 4 mm² / AWG 28 - AWG 12		
rat.wiring strand.AWGmax	0.08 mm² - 2.5 mm² / AWG 28 - AWG 12		
Approvals			
extended wiring UL	2 AWG 16-18, or 1 AWG 16 stranded with 1 AWG 18 solid, or 1 AWG 16 stranded with 1 AWG 18 stranded		
 V / A / AWG	600 / 16 / 28 - 12		
approval UL - File No.	E121004		
 2.5 mm²	630 V / 6 kV / 13.5 A		
Material			
insulating material	PA66		
flammability class	V0		
contact material	CuSn		
Contact surface	Sn		
terminal body thread	M3		
terminal body material	CuZnPb		
terminal body surface	Ni		

U | Contact

Data sheet

RP03AxxHBLC Type 213

Page 3/6

P/N

312132xx

xx=number of poles

2023/06/26

Version: M

Technical Data

screw thread	M3
screw material	8,8
screw surface	Zn Cr(VI)-frei/free
Glow-Wire Flammability GWFI	960 °C acc. to IEC 60695-2-12
Glow-Wire Flammability GWIT	775 °C acc. to IEC 60695-2-13

Climatic Data

upper limit temperature	105 °C
lower limit temperature	-40 °C

general

Tolerance	ISO 2768 -mH
-----------	--------------

U | Contact

Data sheet

RP03AxxHBLC Type 213

Page 4/6

P/N

312132xx

xx=number of poles

2023/06/26

Version: M

Accessories

P/N	Designation
700025-01-9	Coding star white with a group of 6 coding pins



U | Contact

Data sheet

RP03AxxHBLC Type 213

Page 5/6

P/N

312132xx

xx=number of poles

2023/06/26

Version: M

Counterpart

P/N	Designation
311782	PR06AxxHBBN Typ 178
311792	PR06AxxVBBN Typ 179
312192	PT11AxxVBEC Type 219
312202	PT11AxxVBBN Type 220
312292	PT11AxxHBEC Type 229
312302	PT11AxxHBBN Type 230

U | Contact

Data sheet

RP03AxxHBLC Type 213

Page 6/6

P/N

312132xx


xx=number of poles

2023/06/26

Version: M

Illustrations

Dimensional drawing



$L = (\text{pole size} - 1) \times \text{centerline} + 5.08 \text{ mm} [0.2]$

