

## CONNECT

### P | Cabling

We realize ideas

**Data sheet** 

OpDAT FAST<sup>™</sup> Hybrid connector kit SC UPC OS2 100 pieces for cables incl. tool

Page 1/5


P/N 1509QKEO010C-E EAN 4251394625386

> 2023/11/21 Version: G

#### Illustrations



#### Dimensional drawing



See enlarged drawings at the end of document

#### **Product specification**

- Field-attachable fiber optic connector for single-mode technology
- · with hybrid technology: refractive index gel plus opto-elastomer guarantee very good and constant optical values
- no polishing, no gluing during assembly on site
- simple, easy to learn, fast and cost-effective installation in less than two minutes
- Available with connector types LC and SC for singlemode (UPC and APC)
- plug kits for FO fibers with Ø 0.25 and Ø 0.9 mm
- plug kits for fibre optic cables with Ø 2.0 and Ø 3.0 mm
- the plug can be assembled up to three times
- · every plug has a serial number, so that traceability is possible at any time
- Included in the scope of delivery depending on the variant:
- a maintenance-free separator (Cleaver). It provides an oblique cut so that high return loss values are achieved. The Cleaver can be used up to 200 times.
- · a cable assembly kit for easy cable assembly
- · a fiber guide for easy insertion of the fiber into the connector
- · fields of application:
- for FTTH and FITH connections, repairs in the field, in areas which are difficult to access or limited in space and for direct mounting on components
- · Versions for fibers: 10 pieces without tools / 20 or 100 pieces with Cleaver and fibre guide
- · Variants for cables: 10 pieces without tools / 20 or 100 pieces with Cleaver, cable assembly set and fibre guide







We realize ideas

# Data sheet OpDAT FAST<sup>TM</sup> Hybrid connector kit SC UPC OS2 100 pieces for cables incl. tool

Page 2/5

P/N 1509QKEO010C-E EAN 4251394625386

> 2023/11/21 Version: G

General Data	
Fields of application	structured building cabling Consolidation points office areas fiber to the desk Distributed building services data center
Mechanical measurement according to MICE	M1
Ingress measurement according to MICE	I1
Climatic measurement according to MICE	C1
Electromagnetic measurement according to MICE	E3
Design	plug, field assambly
Transmission technology	Fiber optic
Color	blue
Dimensions	
Dimension (L x W x H)	65 mm x 8.99 mm x 7.39 mm
Dimension (L x W x H)	2.559 in. x 0.354 in. x 0.291 in.
Mode type of the fiber	Singlemode
Shape	UPC (Ultra Physical Contact)
Connections/interfaces	
Connector technology interface 1	mechanical splice, fibre cut diagonally
Connector technology interface 2	SC
Single fibre diameter (min max.)	
Single fibre diameter	3 mm
Cable access/outlet	180°
Electrical characteristics	
Insertion loss	0,2 bis 0,5 dB
Return loss	min. 50 dB







We realize ideas

# Data sheet OpDAT FAST<sup>TM</sup> Hybrid connector kit SC UPC OS2 100 pieces for cables incl. tool

Page 3/5

P/N 1509QKEO010C-E EAN 4251394625386

> 2023/11/21 Version: G

Mechanical data Connector type simplex Mounting method snap-in function Life - Number of mating cycles min. 500  Materials and material properties Material - Housing Plastics Material - Cable boot elastomer, flame-retardant and halogen free Material - Ferrule Ceramic Material - Dust protection elastomer, flame-retardant and halogen free Halogen free yes  Environmental conditions	
Connector type simplex  Mounting method snap-in function  Life - Number of mating cycles min. 500  Materials and material properties  Material - Housing Plastics  Material - Cable boot elastomer, flame-retardant and halogen free  Material - Ferrule Ceramic  Material - Dust protection elastomer, flame-retardant and halogen free  Halogen free yes	
Mounting method snap-in function Life - Number of mating cycles min. 500  Materials and material properties  Material - Housing Plastics Material - Cable boot elastomer, flame-retardant and halogen free  Material - Ferrule Ceramic  Material - Dust protection elastomer, flame-retardant and halogen free  Halogen free yes	
Life - Number of mating cycles min. 500  Materials and material properties  Material - Housing Plastics  Material - Cable boot elastomer, flame-retardant and halogen free  Material - Ferrule Ceramic  Material - Dust protection elastomer, flame-retardant and halogen free  Halogen free yes	
Materials and material propertiesMaterial - HousingPlasticsMaterial - Cable bootelastomer, flame-retardant and halogen freeMaterial - FerruleCeramicMaterial - Dust protectionelastomer, flame-retardant and halogen freeHalogen freeyes	
Material - Housing Plastics  Material - Cable boot elastomer, flame-retardant and halogen free  Material - Ferrule Ceramic  Material - Dust protection elastomer, flame-retardant and halogen free  Halogen free yes	
Material - Cable boot elastomer, flame-retardant and halogen free  Material - Ferrule Ceramic  Material - Dust protection elastomer, flame-retardant and halogen free  Halogen free yes	
Material - Ferrule Ceramic  Material - Dust protection elastomer, flame-retardant and halogen free  Halogen free yes	
Material - Dust protection elastomer, flame-retardant and halogen free Halogen free yes	
Halogen free yes	
·	
Environmental conditions	
Temperature (min max.)	
Temperature - Storage °C -25 °C - 70 °C	
Temperature - Storage °F -13 °F - 158 °F	
Temperature - Operating °C -25 °C - 70 °C	
Temperature - Operating °F -13 °F - 158 °F	
Standards/Regulations	
FO connector interfaces IEC 61754-4 / ANSI/TIA-604-3	
Fibre optic connector interfaces IEC 61754-4	
Classifications	
ETIM 7.0 EC001122	
ETIM 8.0 EC001122	
ETIM 9.0 EC001122	
Packing details	
Type of packaging 100 pc(s) / box	









We realize ideas

Data sheet
OpDAT FAST<sup>TM</sup> Hybrid connector kit SC UPC OS2
100 pieces for cables incl. tool

Page 4/5

P/N 1509QKEO010C-E EAN 4251394625386

> 2023/11/21 Version: G

#### **Accessories**

P/N	Designation
150800200-E	Fibre optic tool Bag







We realize ideas

**Data sheet** 

OpDAT FAST<sup>™</sup> Hybrid connector kit SC UPC OS2 100 pieces for cables incl. tool

Page 5/5

P/N 1509QKEO010C-E EAN 4251394625386

> 2023/11/21 Version: G

#### Illustrations

Dimensional drawing

64.68 [2.546]

9.2 [.362]

