

P | Cabling

Data sheet

E-DAT C6 6x8 1RU Modul Cat.6

Page 1/9

P/N

860018-11-E

EAN 4250184111771


2023/04/18

Version: AE


Illustrations



Dimensional drawing



Wiring diagram



See enlarged drawings at the end of document

Product specification

- 6 port module housing made of zinc die-casting for mounting in top hat rail adapter, AP empty housing or 1RU 6 port module frame
- certified to GHMT Cat.6 12C-de-embedded
- compliance with class E_A according to ISO/IEC 11801, DIN EN 50173-1
- tested: Link to 500 MHz
- suitable for 10 GBit Ethernet (IEEE 802.3an), Remote Powering (PoE, PoE plus, UPoE and 4PPoE) and HDBaseT
- wire pairs can be led to the LSA terminal without untwisting the pair
- connection of 2 to 4-pair data lines to LSA insulation displacement connectors (AWG 22-24) conductor colors marking to TIA/EIA 568A
- optional strain relief using cable ties
- incl. 30 cm grounding cable
- grounding bolt M6 x 10 with nut and lock washer



P | Cabling

Data sheet

E-DAT C6 6x8 1RU Modul Cat.6

Page 2/9

P/N

860018-11-E

EAN 4250184111771

2023/04/18

Version: AE

Technical Data

General Data

Fields of application	structured building cabling office areas Distributed building services data center
Mechanical measurement according to MICE	M1
Ingress measurement according to MICE	I1
Climatic measurement according to MICE	C1
Electromagnetic measurement according to MICE	E2
Design	patch panel
Mounting style	1RU
Shielding	shielded
Transmission technology	Copper
Wiring	T568A, T568B
Color	gray
Dimensions	
Dimension (L x W x H)	105.3 mm x 110 mm x 26.1 mm
Dimension (L x W x H)	4.146 in. x 4.331 in. x 1.028 in.
Height unit	1RU

Transmission characteristics

Category (ISO)	6
Class (ISO/IEC)	E _A
Category (TIA)	6
Remote Powering	yes
PoE	IEEE 802.3af
PoE plus	IEEE 802.3at
UPoE	yes
4PPoE	IEEE 802.3bt
HDBaseT	yes
Transmission rate up to 100 MBit (Fast Ethernet)	IEEE 802.3bw
Transmission rate up to 1 GBit (Fast Ethernet)	IEEE 902.3ab
Transmission rate up to 10 GBit	IEEE 802.3an



P | Cabling

Data sheet

E-DAT C6 6x8 1RU Modul Cat.6

Page 3/9

P/N

860018-11-E

EAN 4250184111771

2023/04/18

Version: AE

Technical Data

Connections/interfaces

Connector technology interface 1	LSA terminal block
Connector technology interface 2	RJ45-jack
Number of ports interface 2	6
Number of ports interface 2 equipped	6
Number of positions/contacts interface 1	6 x 8
Number of positions/contacts interface 2	6 x 8P/8C
Termination data, solid wire (min. - max.)	
Conductor cross section, solid wire	AWG 26/1 - AWG 22/1
Conductor cross section, solid wire	0.128 mm ² - 0.324 mm ²
Conductor diameter, solid wire (bare copper)	0.409 mm - 0.643 mm
Conductor diameter, solid wire (bare copper)	0.016 in. - 0.025 in.
Cable access/outlet	180°
Shield connection	flexible contact spring

Electrical characteristics

Current carrying capacity	max. 1 A at 60 °C
Rated voltage	max. 60 V DC
Contact resistance	max. 20 mOhm
Through resistance	max. 200 mOhm
Insulation resistance	min. 500 MOhm
Dielectric strength conductor-conductor (secondary)	max. 1000 V DC
Dielectric strength conductor-conductor, peak value (secondary)	max. 1.000 V AC
Dielectric strength conductor-shield	max. 1500 V DC
Dielectric strength conductor-shield, peak value	max. 1500 V AC

Mechanical data

Insertion and withdrawal force	max. 30 N
Life - Number of mating cycles	min. 750
Position/mounting of latch standard installation position	top
strain relief	cable bracket



P | Cabling

Data sheet

E-DAT C6 6x8 1RU Modul Cat.6

Page 4/9

P/N

860018-11-E

EAN 4250184111771

2023/04/18

Version: AE

Technical Data

Materials and material properties

Material - Terminal block housing	PBT (polybutylene terephthalate)
Material - Jack contact	Hyper Ph-Br
Material - Jack contact finish	AuCo
Material - Terminal block contact	CuSn6
Material - Terminal block contact finish	Sn (tin)
Material - Jack shield	CuSn6
Material - Cover	GD-Zn (zinc die-cast)
Halogen free	yes
RoHS	compliant

Environmental conditions

Temperature (min. - max.)	
Temperature - Storage °C	-40 °C - 70 °C
Temperature - Storage °F	-40 °F - 158 °F
Temperature - Operating °C	-40 °C - 70 °C
Temperature - Operating °F	-40 °F - 158 °F

Certifications

GHMT Type Approval		Component
--------------------	---	-----------

Standards/Regulations

Generic cabling systems	
General requirements	ISO/IEC 11801-1:2017-11 DIN EN 50173-1:2018-10 ANSI/TIA-568.2-D
Office buildings	ISO/IEC 11801-2:2017-11 DIN EN 50173-2:2018-10 ANSI/TIA-568.2-D
Living units	ISO/IEC 11801-4:2017-11 DIN EN 50173-4:2018-10 ANSI/TIA-570-D
Data centers	ISO/IEC 11801-5:2017-11 DIN EN 50173-5:2018-10 ANSI/TIA-942-B



P | Cabling

Data sheet

Page 5/9

E-DAT C6 6x8 1RU Modul Cat.6

P/N

860018-11-E

EAN 4250184111771

2023/04/18

Version: AE

Technical Data

Standards/Regulations

Connectors for electronic equipment

Free and fixed connectors

DIN EN 60603-7-51:2011-01, DIN EN 60603-7:2019-11, DIN EN 60603-7-1:2012-01

Connectors for electronic equipment - Tests and measurements

Test standard for connectors (engaging and separating connectors under electrical load)

DIN-EN 60512-99-001, DIN-EN 60512-99-002

Endurance tests

DIN EN 60603-7:2019-11, DIN EN 60603-7-1:2012-01

Climate tests

DIN EN 60603-7:2019-11, DIN EN 60603-7-1:2012-01

Classifications

ETIM 5.0

EC001128

ETIM 6.0

EC001128

ETIM 7.0

EC001128

ETIM 8.0

EC001128

ETIM 9.0

EC001128

Packing details

Type of packaging

1 pc(s) / box

Packaging unit - Weight (gram)

429 g

Packaging unit - Weight (pound)

0.95 lb

Packaging dimension

139 mm x 115 mm x 37 mm

Packaging dimension

5.472 in. x 4.528 in. x 1.457 in.



P | Cabling

Data sheet

Page 6/9

E-DAT C6 6x8 1RU Modul Cat.6

P/N

860018-11-E

EAN 4250184111771

2023/04/18

Version: AE

Accessories

P/N	Designation
130862-00-E	Module housing 6x8 AP, gray
130862-20-E	Module housing 6x8 AP, pure white



P | Cabling

Data sheet

Page 7/9

E-DAT C6 6x8 1RU Modul Cat.6

P/N

860018-11-E

EAN 4250184111771

2023/04/18

Version: AE

Accessories from

P/N	Designation
130B10E2-E	Module frame 3RU, 7HP 6 port, aluminum, unequipped
854544-E	Module frame 1RU 19 inch, unequipped
854568-E	Module frame 10 inch 1RU

P | Cabling

Data sheet

E-DAT C6 6x8 1RU Modul Cat.6

Page 8/9

P/N

860018-11-E


EAN 4250184111771

2023/04/18


Version: AE

Illustrations

Dimensional drawing



Wiring diagram



P | Cabling

Data sheet

E-DAT C6 6x8 1RU Modul Cat.6

Page 9/9

P/N

860018-11-E


EAN 4250184111771

2023/04/18

Version: AE


Illustrations

Wiring diagram



T568A

Wiring diagram



T568B

