

# CONNECT

#### P | Cabling

We realize ideas

Data sheet

**OpDAT REG K Connect for 12 splice connections** with crimp splice holder

Page 1/4

P/N 15024K0B200-E EAN 4251394628776

> 2023/04/25 Version: D

#### Illustrations



# Dimensional drawing | 128.73 [5.068] | 138. [5.43] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [5.07] | 128.73 [

See enlarged drawings at the end of document

#### **Product specification**

- · Very compact housing for TH35 mounting rail for up to 12 splice connections
- prepared for the connection of two installation cables
- Splice tray with crimp or shrink splice holder
- · different installation variants on the mounting rail are possible
- · Cable feed from above and below
- · 2 cable entries M20 with strain relief included in delivery
- Housing (W x H x D): 50 x 85 x 130 mm
- · Variants: with crimp splice holder for 12 splices or with shrink splice holder for 12 splices







## P | Cabling

We realize ideas

# Data sheet OpDAT REG K Connect for 12 splice connections with crimp splice holder

Page 2/4

P/N 15024K0B200-E EAN 4251394628776

> 2023/04/25 Version: D

|   | Version:   |  |
|---|--|--|
| Technical Data                                |  |  |
| General Data                                  |  |  |
| Fields of application                         | structured building cabling office areas data center |  |
| Mechanical measurement according to MICE      | M1   |  |
| Ingress measurement according to MICE         | I1   |  |
| Climatic measurement according to MICE        | C1   |  |
| Electromagnetic measurement according to MICE | E3   |  |
| Design  | Splice distributor                                   |  |
| Mounting style                                | Standard rail TH35                                   |  |
| Transmission technology                       | Fiber optic  |  |
| Color   | gray   |  |
| Dimensions                                    |  |  |
| Dimension (L x W x H)                         | 145.3 mm x 139 mm x 50 mm                            |  |
| Dimension (L x W x H)                         | 5.72 in. x 5.472 in. x 1.969 in.                     |  |
| Connections/interfaces                        |  |  |
| Number of blind                               | 4  |  |
| Cable access/outlet                           | from top or bottom                                   |  |
| Mechanical data                               |  |  |
| Cut-out                                       | SC-D, LC-Q, ST-D                                     |  |
| Life - Number of mating cycles                | min. 500   |  |
| strain relief                                 | M gland  |  |
| Materials and material properties             |  |  |
| Material - Housing                            | sheet steel  |  |
| Material - Housing finish                     | powder-coated  |  |
| Material - Sleeve                             | ceramic, slotted                                     |  |
| Material - Coupler housing                    | GD-Zn (zinc die-cast)                                |  |
| Halogen free                                  | yes  |  |
| RoHS  | compliant  |  |







## P | Cabling

We realize ideas

Data sheet
OpDAT REG K Connect for 12 splice connections
with crimp splice holder

Page 3/4

P/N 15024K0B200-E EAN 4251394628776

> 2023/04/25 Version: D

| Technical Data  |          |  |
|-----------------|----------|--|
| Classifications |          |  |
| ETIM 7.0        | EC001130 |  |
| ETIM 8.0        | EC001130 |  |
| ETIM 9.0        | EC001130 |  |





### P | Cabling

We realize ideas

Data sheet
OpDAT REG K Connect for 12 splice connections
with crimp splice holder

Page 4/4

P/N 15024K0B200-E

EAN 4251394628776

2023/04/25 Version: D

#### Illustrations

Dimensional drawing



