

Data sheet

PT11AxxHBBF Type 236

Page 1/5

P/N

312362xx

xx=number of poles


2023/06/26

Version: W


Illustrations



Dimensional drawing



Drill pattern



See enlarged drawings at the end of document

Product specification

- pin header, solderable
- centerline 10.16 mm, direction of connection 90°
- closed ends
- color black, mounting flange



U | Contact

Data sheet

PT11AxxHBBF Type 236

Page 2/5

P/N

312362xx

xx=number of poles

2023/06/26

Version: W

Technical Data

General Data

Solder pin length	3.45 mm		
min. number of poles	2		
max. number of poles	12		
Insulating material class	CTI 600		
clearance/creepage dist.	9.18 mm		
Protection category	IP00		
Rated current	10 A		
Overvoltage category	III	III	II
Pollution degree	3	2	2
Rated voltage	630 V	1000 V	1000 V
Rated test voltage	8 kV	8 kV	8 kV

Approvals

V / A

approval UL - File No.	600 / 15 E121004
------------------------	---------------------


1.5 mm²

630 V / 6 kV / 13.5 A / 1.0 x 1.0 mm

Material

insulating material	PA66
flammability class	V0
contact pin material	CuFe
contact pin surface	Ni + Ag
Thread insert	CuZnPb
Glow-Wire Flammability GWFI	960 °C acc. to IEC 60695-2-12
Glow-Wire Flammability GWIT	775 °C acc. to IEC 60695-2-13

Climatic Data

upper limit temperature	105 °C
lower limit temperature	-40 °C

general

Tolerance	ISO 2768 -mH
Solderability	Acc. to JEDEC JESD22-B102E 245°C/5s



U | Contact

Data sheet

Page 3/5

PT11AxxHBBF Type 236

P/N

312362xx**xx=number of poles**

2023/06/26

Version: W

Counterpart of

P/N	Designation
312172	RP03AxxHBLF Type 217
312182	RP03AxxHBLS Type 218
312512	RP01AxxVBLF Type 251

U | Contact

Data sheet

PT11AxxHBBF Type 236

Page 4/5

P/N

312362xx


xx=number of poles

2023/06/26

Version: W

Illustrations

Dimensional drawing



$L = (\text{pole size} - 1) \times \text{centerline} + 14.99 \text{ mm} [0.59]$

U | Contact

Data sheet

PT11AxxHBBF Type 236

Page 5/5

P/N

312362xx

xx=number of poles

2023/06/26

Version: W

Illustrations

Drill pattern

