

Data sheet

PR044xxVBBF Type 391

Page 1/6

P/N


313911xx

xx=number of poles


2023/06/28

Version: X


Illustrations



Dimensional drawing



Drill pattern



See enlarged drawings at the end of document

Product specification

- pin header, THR solderable
- centerline 3.81 mm, direction of connection vertical 0°
- closed ends
- color black, mounting flange
- Tape & Reel packaging possible
- codeable



U | Contact

Data sheet PR044xxVBBF Type 391

Page 2/6

P/N
313911xx

xx=number of poles

2023/06/28

Version: X

Technical Data

General Data

Solder pin length	3.25 mm		
min. number of poles	2		
max. number of poles	16		
Insulating material class	CTI 600		
clearance/creepage dist.	3.01 mm		
Protection category	IP00		
Rated current	10 A		
Overvoltage category	III	III	II
Pollution degree	3	2	2
Rated voltage	200 V	500 V	500 V
Rated test voltage	4 kV	4 kV	4 kV

Approvals

 V / A	300 / 8
approval UL - File No.	E121004
 1.5 mm ²	130 V / 250 kV / 10 A / 0.8 x 0.8 mm

Material

insulating material	PA46
flammability class	V0
contact pin material	CuMg
contact pin surface	Ni + Sn
Glow-Wire Flammability GWFI	-
Glow-Wire Flammability GWIT	-

Climatic Data

upper limit temperature	260 °C
lower limit temperature	-40 °C

general

Tolerance	ISO 2768 -mH
Solderability	reflowable

U | Contact

Data sheet

PR044xxVBBF Type 391

Page 3/6

P/N

313911xx

xx=number of poles

2023/06/28

Version: X

Accessories

P/N	Designation
720293-01-2	Coding Star for pin header, centerline 3.81 mm

U | Contact

Data sheet

PR044xxVBBF Type 391

Page 4/6

P/N

313911xx

xx=number of poles

2023/06/28

Version: X

Counterpart of

P/N	Designation
313791	RP034xxVBLF Type 379
ASP084	SP064xxVGNF ASP084

U | Contact

Data sheet

PR044xxVBBF Type 391

Page 5/6

P/N

313911xx


xx=number of poles

2023/06/28

Version: X

Illustrations

Dimensional drawing



$L = (\text{pole size} - 1) \times \text{centerline} + 13.95 \text{ mm} [0.549]$



U | Contact

Data sheet

PR044xxVBBF Type 391

Page 6/6

P/N

313911xx

xx=number of poles

2023/06/28

Version: X

Illustrations

Drill pattern

