

Data sheet PM20CxxVBNN


Page 1/5

P/N
PM20CXXVBNN
xx=number of poles
2023/07/03
Version: X


Illustrations



Dimensional drawing



PCB-Layout



See enlarged drawings at the end of document

Product specification

- pin header, SMT solderable
- centerline 2.00 mm, direction of connection vertical 0°
- color black
- Tape & Reel packaging possible
- single row



Technical Data

General Data

min. number of poles	2
max. number of poles	40
Rated current	1 A

Material

insulating material	PE-HT
contact pin material	CuZn
contact pin surface	Ni + Au Flash
Glow-Wire Flammability GWFI	-
Glow-Wire Flammability GWIT	-

Climatic Data

upper limit temperature	105 °C
lower limit temperature	-40 °C


general

Tolerance	ISO 2768 -mH
Solderability	reflowable

© 2023 METZ CONNECT - Technische Änderungen vorbehalten! Subject to modifications! Sous réserve de modifications techniques!

Illustrations


Dimensional drawing



$L = (\text{pole size} - 1) \times \text{centerline} + 2 \text{ mm } [0.079]$

Illustrations

PCB-Layout



U | Contact

Data sheet
PM20CxxVBNN

Page 5/5

P/N
PM20CXXVBNN
xx=number of poles
2023/07/03
Version: X

Illustrations