


Data sheet SP066xxVBPC


Page 1/6

P/N
SP066XXVBPC
xx=number of poles
2023/07/03
Version: R

Illustrations



Dimensional drawing



See enlarged drawings at the end of document

Product specification

- spring clamp terminal block, pluggable
- centerline 5.08 mm, direction of connection vertical 0°
- fittable without loss of poles
- color black
- finger push-button, wire entry uncodeable side parallel to plug direction



U | Contact

Data sheet SP066xxVBPC

Page 2/6

P/N
SP066XXVBPC
xx=number of poles
2023/07/03
Version: R

Technical Data

General Data

min. number of poles	2		
max. number of poles	24		
Insulating material class	CTI 600		
clearance/creepage dist.	3.58 mm		
Protection category	IP20		
Min. insul. strip length	10 mm		
Rated current	12 A		
Overvoltage category	III	III	II
Pollution degree	3	2	2
Rated voltage	250 V	630 V	630 V
Rated test voltage	4 kV	4 kV	4 kV

Terminal data

rat.wiring solid AWGmax	0.08 mm ² - 2.5 mm ² / AWG 28 - AWG 12
rat.wiring strand.AWGmax	0.08 mm ² - 2.5 mm ² / AWG 28 - AWG 12

Approvals

 V / A / AWG	300 / 12 / 28 - 12
approval UL - File No.	E121004
 2.5 mm ²	250 V / 4 kV / 12 A

Material

insulating material	PA66
flammability class	V0
spring material	Spring steel
contact material	CuSn
Contact surface	Sn
Glow-Wire Flammability GWFI	960 °C acc. to IEC 60695-2-12
Glow-Wire Flammability GWIT	775 °C acc. to IEC 60695-2-13

Climatic Data

upper limit temperature	105 °C
lower limit temperature	-40 °C

general

U | Contact

Data sheet
SP066xxVBPC

Page 3/6

P/N
SP066XXVBPC
xx=number of poles
2023/07/03
Version: R

Technical Data

Tolerance	ISO 2768 -mH
-----------	--------------



U | Contact

Data sheet
SP066xxVBPC

Page 4/6

P/N
SP066XXVBPC
xx=number of poles
2023/07/03
Version: R

Accessories

P/N	Designation
700025-01-5	Kodierstern blau mit 6 Kodierstiften F_Kodier_blp
700025-01-9	Coding star white with a group of 6 coding pins
840020-02	Drahtbrücke 0.8 RM 5.0 Drahtbrücke 0.8 RM 5.0



U | Contact

Data sheet
SP066xxVBPC

Page 5/6

P/N
SP066XXVBPC
xx=number of poles
2023/07/03
Version: R

Counterpart

P/N	Designation
312191	PT116xxVBEC Type 219
312201	PT116xxVBBN Type 220
314781	PR066xxHBEC Type 478
314791	PR066xxVBEC Type 479



U | Contact


Data sheet
SP066xxVBPC

Page 6/6

P/N
SP066XXVBPC
xx=number of poles
2023/07/03
Version: R

Illustrations

Dimensional drawing



$L = (\text{pole size} - 1) \times \text{centerline} + 5.08 \text{ mm } [0.2]$

