


Data sheet

DCCS subassembly OM5 6xLC-Duplex

Illustrations



Dimensional drawing



See enlarged drawings at the end of document

Product specification

- DCCS housing with 6 LC duplex adapters front mounted
- easy assembly/disassembly in DCCS subrack (19 inch, 1 RU)
- suitable for the installation of pre-terminated installation cables (VIK) with mini breakout cables in customer specific lengths
- housing: galvanized sheet steel, stainless steel front, strain relief via M20 cable gland
- variants: blue (SM), green (SM APC), lime green (OM5), violet (OM4), aqua (OM3)
- all available variants can be created with the configurator

P | Cabling

Data sheet

Page 2/5

DCCS subassembly OM5 6xLC-Duplex

P/N

130D208J00000N

EAN 4251394644912

2023/04/26

Version: C

Technical Data

General Data

Fields of application	structured building cabling office areas data center
Mechanical measurement according to MICE	M1
Ingress measurement according to MICE	I1
Climatic measurement according to MICE	C1
Electromagnetic measurement according to MICE	E3
Design	subassembly / assembly / module / unit
Mounting style	DCCS
Transmission technology	Fiber optic
Port numbering	yes
Color	lime green
Dimensions	
Dimension (L x W x H)	186.6 mm x 53.5 mm x 39.6 mm
Dimension (L x W x H)	7.346 in. x 2.106 in. x 1.559 in.
Inches	19 inches
Fiber class	for OM5
Mode type of the fiber	Multimode

Connections/interfaces

Connector technology interface 1	LC-D Couplers
Number of ports interface 1	6
Number of equipped ports interface 1	6
Number of ports with dust protection interface 1	6
Number of ports with dust protection interface 2	6

Mechanical data

Cut-out	DCCS
Connector type	duplex
Life - Number of mating cycles	min. 1000
strain relief	yes

P | Cabling

Data sheet

Page 3/5

DCCS subassembly OM5 6xLC-Duplex

P/N

130D208J00000N

EAN 4251394644912

2023/04/26

Version: C

Technical Data

Materials and material properties

Material - Assembly housing	sheet steel
Material - Assembly housing finish	Zn (zinc)
Material - Sleeve	ceramic, slotted
Material - Coupler housing	Plastics
Halogen free	yes
RoHS	compliant

Classifications

ETIM 5.0	EC002697
ETIM 6.0	EC002699
ETIM 7.0	EC001129
ETIM 8.0	EC001129
ETIM 9.0	EC001129

Packing details

Type of packaging	1 pc(s) / box
-------------------	---------------

P | Cabling

Data sheet

Page 4/5

DCCS subassembly OM5 6xLC-Duplex

P/N

130D208J00000N

EAN 4251394644912

2023/04/26

Version: C

Accessories

P/N	Designation
130D2B1B-E	DCCS2 BGT 19 inch 1RU subrack black
130D2B1G-E	DCCS2 BGT 19 inch 1RU subrack light gray

© 2023 METZ CONNECT - Technische Änderungen vorbehalten! Subject to modifications! Sous réserve de modifications techniques!



P | Cabling

Data sheet

Page 5/5

DCCS subassembly OM5 6xLC-Duplex

P/N

130D208J00000N

EAN 4251394644912

2023/04/26

Version: C

Illustrations

Dimensional drawing

