

P | Cabling

Data sheet

OpDAT REGpro front cover 6xLC-Q UPC OS2

Page 1/5

P/N


15024A7106-E

EAN 4250184161103


2023/04/19

Version: Z

Illustrations



Dimensional drawing



See enlarged drawings at the end of document

Product specification

- front plate 3RU/7HP LC-Q adapters
- slotted ceramics sleeve for single mode and multi mode applications
- suitable for mounting in OpDAT REGpro24 and OpDAT REG S
- gray, powder-coated steel sheet
- variants: equipped with 3 or 6 LC-Q adapters, each in blue (OS2), violet (OM4), aqua (OM3) or LC-Q APC adapters, each in green (OS2)



P | Cabling

Data sheet

Page 2/5

OpDAT REGpro front cover 6xLC-Q UPC OS2

P/N

15024A7106-E

EAN 4250184161103

2023/04/19

Version: Z

Technical Data

General Data

Fields of application	structured building cabling office areas data center
Mechanical measurement according to MICE	M1
Ingress measurement according to MICE	I1
Climatic measurement according to MICE	C1
Electromagnetic measurement according to MICE	E3
Design	front plate
Mounting style	3RU/7HP
Transmission technology	Fiber optic
Color	blue
Dimensions	
Dimension (L x W x H)	30.7 mm x 128.9 mm x 35.3 mm
Dimension (L x W x H)	1.209 in. x 5.075 in. x 1.39 in.
Height unit	3RU
Horizontal pitch	7HP
Mode type of the fiber	Singlemode
Shape	UPC (Ultra Physical Contact)
Fiber construction	9/125 µm

Connections/interfaces

Connector technology interface 1	LC-Q Couplers
Connector technology interface 2	LC-Q Couplers
Number of ports interface 1	6
Number of ports interface 2	6
Number of equipped ports interface 1	6
Number of ports interface 2 equipped	6
Number of ports with dust protection interface 1	6
Number of ports with dust protection interface 2	6

Mechanical data

Cut-out	SC-D, LC-Q, ST-D
Life - Number of mating cycles	min. 1000



P | Cabling

Data sheet

Page 3/5

OpDAT REGpro front cover 6xLC-Q UPC OS2

P/N

15024A7106-E

EAN 4250184161103

2023/04/19

Version: Z

Technical Data

Materials and material properties

Material - Mounting plate	steel
Material - Mounting plate finish	powder-coated
Material - Sleeve	ceramic, slotted
Material - Coupler housing	Plastics
Halogen free	yes
RoHS	compliant

Classifications

ETIM 5.0	EC001130
ETIM 6.0	EC001130
ETIM 7.0	EC001130
ETIM 8.0	EC001130
ETIM 9.0	EC001130

Packing details

Type of packaging	1 pc(s) / plastic bag
Packaging unit - Weight (gram)	280 g
Packaging unit - Weight (pound)	0.62 lb
Packaging dimension	160 mm x 100 mm x 380 mm
Packaging dimension	6.299 in. x 3.937 in. x 14.961 in.



P | Cabling

Data sheet

Page 4/5

OpDAT REGpro front cover 6xLC-Q UPC OS2

P/N

15024A7106-E

EAN 4250184161103

2023/04/19

Version: Z

Accessories from

P/N	Designation
15024A10-24-E	OpDAT REGpro24 housing without splice tray

P | Cabling

Data sheet

Page 5/5

OpDAT REGpro front cover 6xLC-Q UPC OS2

P/N

15024A7106-E

EAN 4250184161103

2023/04/19

Version: Z

Illustrations

Dimensional drawing

