

Data sheet

OpDAT pre-assembled splice tray 12xSC PC OM2

Page 1/5

P/N


150922E000-E

EAN 4250184174394


2023/06/01

Version: AJ

Illustrations



Dimensional drawing



See enlarged drawings at the end of document

Product specification

- pre-assembled splice tray equipped with 12 pigtailed with SC plugs
- suitable to be mounted in the following fiber optic patch panels: OpDAT fix, OpDAT slide, OpDAT PF and OpDAT PA
- standard splice tray (154.50 x 92 x 10 mm) equipped with crimp splice holder and cover
- 12 semi-tight buffer pigtailed inserted and stripped
- assorted pigtail colors according to IEC 60304, primary and secondary coating in the same color
- with test report, insertion loss and return loss tested at 100 %
- lengths of the pigtailed starting from tray are layered between 80 and 90 cm
- variants: available with fiber types OS2, OM5, OM4, OM3



P | Cabling

Data sheet

Page 2/5

OpDAT pre-assembled splice tray 12xSC PC OM2

P/N

150922E000-E

EAN 4250184174394

2023/06/01

Version: AJ

Technical Data

General Data

Fields of application	data center
Mechanical measurement according to MICE	M1
Ingress measurement according to MICE	I1
Climatic measurement according to MICE	C1
Electromagnetic measurement according to MICE	E3
Design	pre-assembled splice tray
Transmission technology	Fiber optic
Color	beige
Dimensions	
Dimension (L x W x H)	154.5 mm x 10 mm x 92 mm
Dimension (L x W x H)	6.083 in. x 0.394 in. x 3.622 in.
Mode type of the fiber	Multimode
Fiber class	OM2 bend sensitive (ISO/IEC 11801/EN 50173 & IEC 60793-2-10/EN 60793-2-10 A1.a.1)
Cable Type	pigtail(s)
Number of cables/ buffered fibers	12
Number of fibres each cable/ wire	1
Shape	PC (Physical Contact)
Fiber construction	50/125 µm
Minimum length	0.8 m
Minimum length	2.62 ft
Maximum length	0.9 m
Maximum length	2.95 ft

Connections/interfaces

Connector technology interface 2	SC PC
----------------------------------	-------

Optical characteristics

Insertion loss	max. 0,4 dB
Return loss	min. 35 dB

P | Cabling

Data sheet

Page 3/5

OpDAT pre-assembled splice tray 12xSC PC OM2

P/N

150922E000-E

EAN 4250184174394

2023/06/01

Version: AJ

Technical Data

Materials and material properties

Material - Coupler housing	Plastics
Material - Housing	ABS
Bend insensitivity	yes
Halogen free	yes
RoHS	compliant

Standards/Regulations

Generic cabling systems	
General requirements	ISO/IEC 11801
Fibre optic connector interfaces	IEC 61754-4
Optical fibers: Product specifications	
Sectional specification for category A1 multimode fibres	ISO/IEC 60793-2-10 (A1a.1)
Optical fibers - Interconnecting devices and passive components - basic test and measuring methods	
Fibre optic interconnecting devices and passive components	IEC 61300-3-4 IEC 61300-3-6
Standard colours for insulation for low-frequency cables & wires	IEC 60304
ITU-T standard	G.651.1

Classifications

ETIM 5.0	EC001130
ETIM 6.0	EC001130
ETIM 7.0	EC000762
ETIM 8.0	EC000762
ETIM 9.0	EC000762

Packing details

Type of packaging	1 pc(s) / box
Packaging unit - Weight (gram)	127 g
Packaging unit - Weight (pound)	0.28 lb
Packaging dimension	258 mm x 164 mm x 51 mm
Packaging dimension	10.157 in. x 6.457 in. x 2.008 in.

P | Cabling

Data sheet

Page 4/5

OpDAT pre-assembled splice tray 12xSC PC OM2

P/N

150922E000-E

EAN 4250184174394

2023/06/01

Version: AJ

Accessories from

P/N	Designation
1502000200-E	OpDAT PF 1HE Patchfeld festeinbau für 24xSC/LC-D, unbestückt
1502005200-E	OpDAT PF patch panel for 12xSC-Duplex/LC-Q/ST-Duplex
1502007300-E	OpDAT PF patch panel for 24xLC-Duplex/SC-Simplex/E2000-Simplex
1502200200-E	OpDAT PA patch panel unequipped for 24xLC-D/SC-S/E2000, gray
1502205200-E	OpDAT PA patch panel for 12xSC-Duplex/LC-Quad/ST-Duplex
1502507300-E	OpDAT fix patch panel for 24xLC-Duplex/SC-Simplex/E2000
150250B200-E	OpDAT fix patch panel for 24xSC-Duplex/LC-Quad/ST-Duplex



P | Cabling

Data sheet

Page 5/5

OpDAT pre-assembled splice tray 12xSC PC OM2

P/N

150922E000-E


EAN 4250184174394

2023/06/01

Version: AJ

Illustrations

Dimensional drawing



© 2023 METZ CONNECT - Technische Änderungen vorbehalten! Subject to modifications! Sous réserve de modifications techniques!

