

P | Cabling


Data sheet

OpDAT APL extension box splice 2xLC-D UPC OS2 Grade B


Page 1/5

P/N
1501597U02HC
EAN 4251394656052
2023/04/13
Version: E

Illustrations



Dimensional drawing



See enlarged drawings at the end of document

Product specification

- compact fiber optic termination point for the FITH area
- prepared for receiving microtubes with gasblockers
- sealable or lockable by safety screw
- equipped with adapters with laser shutter and pigtails
- pigtails with single mode fiber OS2, E9/125 µm, IEC 60793-2-50 B.1.3 and B.6_a, bend insensitive according to ITU-T G.657.A1, compatible to ITU-T G.652.D
- pigtails are cleaned and plugged in adapters
- unequipped ports are closed with blind plugs
- for surface mounting and with integrated clips for rail mounting in two directions
- pivoting, removable splice tray for up to 8 shrink splice protections
- cover removable without tool
- plug direction 90°
- color of the cover parts pure white RAL 9010
- variants: equipped with SC APC, SC UPC, LC-D APC or LC-D UPC adapters and matching pigtails
- variants also available in Grade B



P | Cabling

Data sheet

Page 2/5

OpDAT APL extension box splice 2xLC-D UPC OS2 Grade B

P/N
1501597U02HC
EAN 4251394656052
2023/04/13
Version: E

Technical Data

General Data	
Fields of application	structured building cabling
Mechanical measurement according to MICE	M1
Ingress measurement according to MICE	I1
Climatic measurement according to MICE	C1
Electromagnetic measurement according to MICE	E3
Design	AP
Mounting style	surface mount, standard rail TH35
Transmission technology	Fiber optic
Color	Pure white RAL 9010
Dimensions	
Dimension (L x W x H)	118 mm x 108 mm x 39 mm
Dimension (L x W x H)	4.646 in. x 4.252 in. x 1.535 in.
Cable Type	pigtail(s)
Mode type of the fiber	Singlemode
Fiber class	OS2: IEC 60793-2-50 B6_a, B6_b & ITU-T G.657.A2, G.657.B2, G.652.D
Shape	UPC (Ultra Physical Contact)
Fiber construction	9/125 µm
Connections/interfaces	
Connector technology interface 1	LC-D
Connector technology interface 2	LC-D
Number of ports interface 1	4
Number of ports interface 2	4
Number of equipped ports interface 1	2
Number of ports interface 2 equipped	2
Number of blind	2
Core diameter (min. - max.)	
	900 µm
	35.433 in.
Cable access/outlet	bottom

P | Cabling

Data sheet

Page 3/5

OpDAT APL extension box splice 2xLC-D UPC OS2 Grade B

P/N
1501597U02HC
EAN 4251394656052
2023/04/13
Version: E

Technical Data

Elektrische/ Optische Eigenschaften	
Insertion loss	max. 0,25 dB
Return loss	min. 50 dB
Mechanical data	
Connector type	duplex
Life - Number of mating cycles	min. 1000
Materials and material properties	
Material - Housing	ABS + PC
Material - Coupler housing	Plastics
Material - Sleeve	ceramic, slotted
Material - Ferrule	Ceramic
Material - Crimp sleeve	Al (Aluminium)
RoHS	compliant
Environmental conditions	
Temperature (min. - max.)	
Temperature - Storage °C	-10 °C - 60 °C
Temperature - Storage °F	14 °F - 140 °F
Temperature - Operating °C	-10 °C - 60 °C
Temperature - Operating °F	14 °F - 140 °F
Particulate ingress	IP2X
Liquid ingress/immersion	IPX0
Classifications	
ETIM 7.0	EC001409
ETIM 8.0	EC001409
ETIM 9.0	EC001409
Packing details	
Type of packaging	1 pc(s) / box

P | Cabling

Data sheet

Page 4/5

OpDAT APL extension box splice 2xLC-D UPC OS2 Grade B

P/N

1501597U02HC

EAN 4251394656052

2023/04/13

Version: E

Accessories

P/N	Designation
15090304-I	OpDAT splice protection cover for 6 crimp splices
15090401-E	OpDAT crimp splice protection (12 pieces)



P | Cabling

Data sheet

OpDAT APL extension box splice
2xLC-D UPC OS2 Grade B

Page 5/5

P/N
1501597U02HC
 EAN **4251394656052**
 2023/04/13
 Version: E

Illustrations

Dimensional drawing

