

Data sheet

MC274-4W 24 V AC


Page 1/6

P/N
110017101407
EAN 4251122194887
2023/06/23
Version: B


Illustrations



Wiring diagram



Diagramm



See enlarged drawings at the end of document

Product specification

Compact, pluggable relay for industrial use.

- Socket pins as soldering lugs
- Mechanical switch position display
- With manual test button
- Cadmium-free contacts
- LED-Indicator



Data sheet MC274-4W 24 V AC

Page 2/6

P/N
110017101407
EAN 4251122194887
2023/06/23
Version: B

Technical Data

Supply

Operating voltage	24 V AC -10% ... +10%
Power consumption (max.)	67 mA
Response time typical	10 ms
Release time typical	8 ms
Coil resistance	158 Ohm

Outputs

Contacts	4 changeover contacts
Contact material	AgNi
Switching capacity (max.)	1500 VA
Switching frequency	1200 switching cycles/h
Switching voltage (max.)	250 V AC
Switching voltage (min.)	10 V at 30 mA
Switching current (min.)	5 mA
Switching capacity (min.)	300 mW
Continuous Current	7 A
Switch-on current	12 A
Switching capacity	
Switching capacity AC 1	6 A / 250 V AC
Switching capacity AC 14 (at 120 V)	0,6 A (D300)
Switching capacity AC 14 (at 240 V)	0,3 A (D300)
Switching capacity AC 15 (at 120 V)	1.5 A
Switching capacity AC 15 (at 240 V)	0,75 A (C300)0,75 A (C300)
Breaking capacity (resistive load)	
Mechanical life	1x10 ⁷ switching cycles

Insulation coil - contact set

Nominal voltage of the power supply system	250 V AC
Overvoltage category	II
Degree of pollution	2
Rated test voltage	2.5 kV
Type of insulation	basic insulation



Technical Data

Housing

Dimensions

Dimension (W x H x D)	21 mm x 35.5 mm x 27.4 mm
Dimension (W x H x D)	0.827 in. x 1.398 in. x 1.079 in.
Weight	35 g
Mounting style	pluggable
Mounting position	any
Apposition	without distance
Connection type	plug-in connection

Protection category according to IEC 60529

Protection category (acc. to EN 116000-3)	RT I
---	------

Temperature range

Operating

Temperature - Operating °C	-40 °C - 55 °C
Temperature - Operating °F	-40 °F - 131 °F

Storage

Temperature - Storage °C	-40 °C - 85 °C
Temperature - Storage °F	-40 °F - 185 °F

Power loss

Power loss (typical) coil	1.2 W
Power loss (typical) Contact rate	0.4 W

Classifications

ETIM 7.0	EC001437
ETIM 8.0	EC001437
ETIM 9.0	EC001437


Accessories

P/N	Designation
110175	Socket 14 poles
110178	Socket 14 poles for electronic modules
110185	Socket 14 poles with spring-loaded terminals




Illustrations

Wiring diagram



Diagramm



Illustrations

Diagramm

