

Data sheet KD-S12/11A

Page 1/5

P/N
110628

EAN 4250184122753


2023/06/20

Version: B


Illustrations



Dimensional drawing



Wiring diagram



See enlarged drawings at the end of document

Product specification

The diode module is equipped with 11 diodes. The anodes of the diodes are all connected to each other. The module is used for failure indication systems (lamp tests).

- common anode
- Connection with screw-type terminals

Technical Data

Housing

Dimensions

Dimension (W x H x D)	22.5 mm x 75 mm x 95 mm
Dimension (W x H x D)	0.886 in. x 2.953 in. x 3.74 in.
Weight	20 g
Mounting style	Standard rail TH35
Mounting position	any
Apposition	without distance
Connection type	Screw type terminal blocks

Terminal blocks

Wire cross section solid	0.2 mm ² - 2.5 mm ² / AWG 22-12
Wire cross section multi	0.25 mm ² - 2.5 mm ² / AWG 22-12
Wire cross section with wire ferrule	0.25 mm ² - 2.5 mm ² / AWG 22-12
Screw torque (max.)	0.5 Nm
Stripping length (min.)	8 mm

Material

Material - Housing	Polyamid 6.6 V0
Color	gray
Material - Terminal block	Polyamid 6.6 V0
Material - Covers	Polyamid 6.6 V0

Protection category according to IEC 60529

Protection category - housing (acc. to IEC 60529)	IP40
Protection category - terminal blocks (acc. to IEC 60529)	IP20

Temperature range

Operating	
Temperature - Operating °C	-10 °C - 50 °C
Temperature - Operating °F	14 °F - 122 °F
Storage	
Temperature - Storage °C	-25 °C - 70 °C
Temperature - Storage °F	-13 °F - 158 °F



C | Logline

Data sheet
KD-S12/11A

Page 3/5

P/N
110628

EAN 4250184122753

2023/06/20

Version: B

Technical Data


Classifications

ETIM 7.0	EC002878
ETIM 8.0	EC002878
ETIM 9.0	EC002878




Illustrations

Dimensional drawing



Wiring diagram



Illustrations

Circuit diagram

