

P | Cabling

Data sheet

OpDAT CM 6xSC-D OM4 VIK

Page 1/6

P/N

1528S0BB061E

EAN 4251394671246


2023/07/10

Version: A

Illustrations



Dimensional drawing



See enlarged drawings at the end of document

Product specification

- compact module OpDAT CM 6xSC-D 3RU/HP
- fully equipped with 6 SC-D adapters
- for installation of pre-assembled cables
- front panel made of silver anodized aluminum, with numbered adapter positions
- mounting plate made of steel, overlength tray with a cover
- fixing in the subassembly frame by captive screws
- variants: equipped with SC-D adapters in blue (OS2), green (OS2 APC), violet (OM4) or aqua (OM3)



P | Cabling

Data sheet

OpDAT CM 6xSC-D OM4 VIK

Page 2/6

P/N

1528S0BB061E

EAN 4251394671246

2023/07/10

Version: A

Technical Data

General Data

Fields of application	structured building cabling office areas data center
Mechanical measurement according to MICE	M1
Ingress measurement according to MICE	I1
Climatic measurement according to MICE	C1
Electromagnetic measurement according to MICE	E3
Design	Compact module
Mounting style	3RU/7HP
Transmission technology	Fiber optic
Port numbering	yes
Color	violet
Dimensions	
Dimension (L x W x H)	249.6 mm x 128.9 mm x 35.3 mm
Dimension (L x W x H)	9.827 in. x 5.075 in. x 1.39 in.
Inches	19 inches
Height unit	3RU
Horizontal pitch	7HP
Installation depth	242 mm
Installation depth	9.528 in.
Fiber class	OM4
Mode type of the fiber	Multimode
Labeling option	printed numbers

Connections/interfaces

Connector technology interface 1	SC-D Couplers
Number of ports interface 1	6
Number of ports interface 2	6
Number of equipped ports interface 1	6
Number of ports interface 2 equipped	6
Number of ports with dust protection interface 1	6
Number of ports with dust protection interface 2	6



P | Cabling

Data sheet

OpDAT CM 6xSC-D OM4 VIK

Page 3/6

P/N

1528S0BB061E

EAN 4251394671246

2023/07/10

Version: A

Technical Data

Mechanical data

Cut-out	SC-D, LC-Q
Connector type	duplex

Materials and material properties

Material - Front cover	Al (Aluminium)
Material - Front cover finish	silver anodized
Material - Mounting plate	steel
Material - Sleeve	ceramic, slotted
Material - Coupler housing	Plastics
Halogen free	yes
RoHS	compliant

Classifications

ETIM 5.0	EC001130
ETIM 6.0	EC001130
ETIM 7.0	EC001130
ETIM 8.0	EC001130
ETIM 9.0	EC001130

Packing details

Type of packaging	1 pc(s) / box
-------------------	---------------



P | Cabling

Data sheet

Page 4/6

OpDAT CM 6xSC-D OM4 VIK

P/N

1528S0BB061E

EAN 4251394671246

2023/07/10

Version: A

Accessories

P/N	Designation
1528SZ001-E	OpDAT CM Accessories kit 1
1528SZ002-E	OpDAT CM Accessories kit 2

P | Cabling

Data sheet

Page 5/6

OpDAT CM 6xSC-D OM4 VIK

P/N

1528S0BB061E

EAN 4251394671246

2023/07/10

Version: A

Accessories from

P/N	Designation
1528SBGT19-E	OpDAT CM 19 inches/3RU subrack

P | Cabling

Data sheet

OpDAT CM 6xSC-D OM4 VIK

Page 6/6

P/N

1528S0BB061E

EAN 4251394671246

2023/07/10

Version: A

Illustrations

Dimensional drawing

